

EXTERIOR DYE

TOOLS & MATERIALS REQUIRED

- ★ Distilled Water for dilution
- ★ EAGLE ARMOR SEAL
- ★ Sprayer and absorbent cloth or small container to catch drips
- ★ Plastic sheeting and painter's masking tape
- ★ EAGLE ETCH & CLEAN
- ★ EAGLE CLEANER DEGREASER & NEUTRALIZER

SURFACE PREPARATION

The surface should be free of dirt and oil. Clean with EAGLE ETCH & CLEAN to profile and clean the concrete surface. For extremely dirty surfaces, EAGLE CLEANER DEGREASER & NEUTRALIZER is recommended. Rinse with clean water. If possible, power wash the surface at 3000 psi. Allow the surface to dry 24 hours before applying the stain. All walls, furniture, columns, or other items/areas that you do not want to color should be masked using painter's tape and plastic sheeting. This will protect the items from overspray. Always do a test spot in an inconspicuous area before proceeding.

APPLICATION

EAGLE EXTERIOR CONCRETE DYE concentrate should be added to one gallon of Distilled Water in sprayer. Use Distilled Water to rinse color concentrate from bottle. Mix the two ingredients thoroughly. Apply with drip-less, pump-up sprayer using a conical, fine-spray tip. Small areas can be brushed using a circular motion to avoid brush strokes. Take care to maintain a wet edge to avoid lines, and avoid puddling EAGLE EXTERIOR CONCRETE DYE. Avoid drips. If not using a drip-less sprayer, tape a piece of cloth or a small container to the sprayer body to catch drips while not spraying the material. Place the tip of the spray wand on the cloth or into the small container immediately after releasing the spray handle. Apply the stain uniformly to obtain a more even final appearance. Apply in a random, circular motion with some overlapping to generate a more mottled look and more closely resemble acid stain. Depending on the depth of color that is desired, coverage rates will vary.

COVERAGE RATE

Approximately 200-400 square feet per gallon depending on depth of color desired and porosity of concrete. More material will be required for more porous surfaces or deeper coloration, and less for tighter surfaces or if less color is desired.

SEALING

Allow EAGLE EXTERIOR CONCRETE DYE to dry for 12 hours before sealing. Apply EAGLE ARMOR SEAL at approximately 200 square feet per gallon. EAGLE ARMOR SEAL is a low-odor, low-VOC, water-based sealer. Allow to dry for 4 hours for foot traffic and 24 hours for vehicle traffic.

TECHNICAL DATA

VOC: <100 g/l
Flash Point: > 248° F

	HMIS		
Health	1	Flammability	1
Reactivity	0	Protection	H

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Eagle IFP warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in U.S.A

EAGLE IFP COMPANY

www.eaglesealer.com